## **S-2CONNECT Sense**

## **SPEED TO CONNECT**

Features:

- Bluetooth Low Energy
- Long Battery Life
- Slimmed Size
- V4.2, Compliant BLE5
- Temperature
- Humidity
- Accelerometer

# Markets:

- Cold chain
- Asset monitoring
- Environment monitoring
- Smart Home





### **Description:**

S-2CONNECT Sense is a Bluetooth Low Energy (BLE) tag designed to record temperature, humidity and impact data. It uses BLE to transfer the information to the nearest S-2CONNECT Hub. A long battery life time and ruggedized enclosure (IP65) makes it suitable for asset monitoring.

| Communication                | BLE                   | BLE v4.2, compliant v5                  |
|------------------------------|-----------------------|---|
| Frequency Bands              | BLE                   | 2.4 GHz                                 |
| <b>Electrical Properties</b> | Current Consumption   | 35uA beaconing every sec                |
|                              | Battery               | CR2450                                  |
|                              | Processor             | ARM Cortex M4                           |
|                              | Memory/flash          | 256kB / 8MB                             |
|                              | Battery Life          | >1 year (at 25°C, 5min reporting cycle) |
| Sensors Accuracy             | Temperature           | -20°C to +85°C (+/-0.3°C)               |
|                              | Humidity              | 0 - 100% Rh (+/-2% Rh)                  |
|                              | Accelerometer         | +/-2g (+/-2mg/LSB)                      |
|                              | Light                 | Dark/Light sensing*                     |
| Mechanical Properties        | Enclosure IP          | IP65                                    |
|                              | Enclosure Colour      | Transparent or White Option             |
|                              | Outer Dimensions      | 33.0mm x 64.5mm x 9.5mm                 |
|                              | Weight                | 17g (without battery)                   |
|                              | Operating Temperature | -20°C to +85°C                          |
|                              | LED                   | Alarm                                   |
| Software Properties          | Firmware protocols    | Zephyr RTOS                             |

<sup>\*</sup> Transparent enclosure only